DRAINAGE CRITERIA MANUAL

CITY OF
LEWISVILLE
TEXAS

APRIL 1988

DRAINAGE CRITERIA MANUAL
FOR
THE CITY OF LEWISVILLE, TEXAS

Prepared by:

Espey, Huston & Associates, Inc.
17811 Waterview Parkway
Dallas, Texas 75252

April 1988

TABLE OF CONTENTS

Section		Page
	List of Figures	vi
	List of Tables	viii
SECTION 1 - GENERAL DRAINAGE POLICY		1-1
1.01	General	1-1
1.02	Summary of Required Design Frequencies	1-1
1.03	Criteria for Filling In a Floodplain	1-1
1.04	Required Technical Information to be Submitted for City Review	1-3
SECTION 2 - DETERMINATION OF STORM RUNOFF		
2.01	General	2-1
2.02	Effect of Urbanization	2-1
2.03	Rainfall-Runoff Design Frequencies	2-2
2.04	Relating Rainfall to Runoff	2-2
2.05	Rational Method	2-11
SECTION 3 - FLOW IN STREETS		3-1
3.01	General	3-1
3.02	Permissible Spread of Water	3-2
3.03	Minimum and Maximum Velocities	3-4
3.04	Design Method	3-4
SECTION 4 - STORM DRAIN INLETS		4-1
4.01	General	4-1
4.02	Classification	4-1

TABLE OF CONTENTS (Cont'd)

Section		Page
4.03	Inlets in Sags	4-2
4.04	Inlets On Grade Without Gutter Depression	4-4
4.05	Inlets On Grade With Gutter Depression	4-5
SECTION 5	- FLOW IN STORM DRAINS AND THEIR APPURTENANCES	5-1
5.01	General	5-1
5.02	Velocities and Grades	5-1
5.03	Materials	5-2
5.04	Full or Part Full Flow in Storm Drains	5-3
5.05	Hydraulic Gradient and Profile of Storm Drains	5-6
5.06	Manhole Location	5-7
5.07	Pipe Connections	5-7
5.08	Minor Head Losses at Structure	5-7
5.09	Utilities	5-11
SECTION 6	- DESIGN OF ENCLOSED STORM DRAINAGE SYSTEMS	6-1
6.01	General	6-1
6.02	Preliminary Design Considerations	6-1
6.03	Inlet System	6-2
6.04	Storm Sewer System	6-4
SECTION 7	- FLOW IN OPEN CHANNELS	7-1
7.01	General	7-1
7.02	Channel Discharge	7-2

TABLE OF CONTENTS (Cont'd)

Section		Page
7.03	Water Surface Profiles	7-3
7.04	Design Considerations	7-3
7.05	Channel Cross Sections	7-4
7.06	Channel Drops	7-6
7.07	Baffle Chutes	7-7
7.08	Structure Aesthetics	7-7
7.09	Right of Way Required for Open Channels	7-8
7.10	Streets Along Drainageways	7-8
SECTION 8 - DESIGN OF CULVERTS		8-1
8.01	General	8-1
8.02	Quantity of Flow	8-1
8.03	Headwalls and Endwalls	8-1
8.04	Culvert Discharge Velocities	8-4
8.05	Selection of Culvert Size and Type	8-5
SECTION 9 - STORM RUNOFF STORAGE		9-1
9.01	General	9-1
9.02	Master Plans	9-1
9.03	Storage Classification	9-1
9.04	Design Procedures	9-2
9.05	General Requirements for Detention Pond Construction	9-4
9.06	Geotechnical Investigation	9-5
9.07	Required Analyses	9-6
REFERENCES		

TABLE OF CONTENTS (Concluded)

Section

APPENDIX A GLOSSARY OF TERMS

APPENDIX B TEXAS WATER COMMISSION PERMANENT RULE CHANGES

APPENDIX C FLOOD INSURANCE STUDY, CITY OF LEWISVILLE

LIST OF FIGURES

Figure	
2-1	Effect of Watershed Development on Storm Hydrograph
2-2	NUDALLAS Clay Urbanization Curve
2-3	NUDALLAS Sand Urbanization Curve
2-4	Rainfall Curves for Lewisville, Texas
2-5	Average Velocities for Estimating Travel Time for Overland Flow for Lewisville, Texas
3-1	Nomograph for Flow in Triangular Channels
4-1	Inlet Capacity for Low Point Inlets
4-2	Ratio of Intercepted to Total Flow Inlets On Grade
4-3	Capacity for Inlets On Grade
5-1	Uniform Flow for Pipe Culverts
5-2	Critical Depth of Flow for Circular Conduits
5-3	Velocity in Pipe Conduits
5-4	Critical Depth for Elliptical Pipe
5-5	Uniform Flow for Concrete Elliptical Pipe
5-6	Velocity in Elliptical Pipe
5-7	Critical Depth of Flow for Pipe-Arch
5-8	Uniform Flow for Pipe-Arch
5-9	Velocity in Pipe-Arch
5-10	Minor Head Losses Due to Turbulence at Structures
7-1	Uniform Flow for Trapezoidal Channels
8-1	Critical Flow for Box Culverts - n = 0.012
8-2	Uniform Flow for Box Culverts - n = 0.012
8-3	Headwater Depth for Box Culverts With Inlet Control
8-4	Head for Concrete Box Culverts Flowing Full - n = 0.012
8-5	Uniform Flow for Pipe Culverts

LIST OF FIGURES (Concluded)

Figure	
8-6	Critical Depth of Flow for Circular Conduits
8-7	Velocity in Pipe Conduits
8-8	Headwater Depth for Concrete Pipe Culverts with Inlet Control
8-9	Headwater Depth for C.M. Pipe Culverts with Inlet Control
8-10	Head for Concrete Pipe Culverts Flowing Full - n = 0.012
8-11	Head for Standard C.M. Pipe Culverts Flowing Full - n = 0.024
8-12	Critical Depth for Elliptical Pipe
8-13	Uniform Flow for Concrete Elliptical Pipe
8-14	Velocity in Elliptical Pipe
8-15	Headwater Depth for Oval Concrete Pipe Culverts Long Axis Horizontal with Inlet Control
8-16	Head for Elliptical Concrete Pipe Culverts Long Axis Horizontal or Vertical Flowing Full - n = 0.012
8-17	Critical Depth of Flow for Pipe-Arch
8-18	Uniform Flow for Pipe-Arch
8-19	Velocity in Pipe-Arch
8-20	Headwater Depth for C.M. Pipe-Arch Culverts with Inlet Control
8-21	Head for Standard C.M. Pipe-Arch Culverts Flowing Full - n = 0.024
9-1	Preliminary Sizing of Storage Facility

LIST OF TABLES

Table		Page
2-1	Point Rainfall Amount for Varying Durations and Frequencies in Lewisville, Texas	2-16
2-2	Percent Urbanization and Imperviousness Summary with Associated Land Use Categories Recommended Values	2-17
2-3	Nudallas Block and Uniform Loss Rate Recommended Values for Lewisville, Texas	2-18
2-4	Frequency Factor Coefficients for Adjustment of the Rational Method C Value	2-19
2-5	Rational Method Runoff Coefficients for 5-Year Frequency Storm	2-20
4-1	Storm Drain Inlets	4-7
5-1	Minimum Slope Required to Produce Scouring Velocity	5-2
5-2	Maximum Velocity in Storm Drains	5-2
5-3	Roughness Coefficients "n" for Storm Drains	5-3
5-4	Junction or Structure Coefficient of Loss	5-9
5-5	Head Loss Coefficients Due to Obstructions	5-10
5-6	Head Loss Coefficients Due to Sudden Enlargements and Contractions	5-11
7-1	Computation of Composite Roughness Coefficient for Excavated and Natural Channels	7-4
8-1	Values of Entrance Loss Coefficients "K_e"	8-2
8-2	Reduction Factors for Velocity of Approach	8-3
8-3	Culvert Discharge - Velocity Limitations	8-4